

Butyl & High Performance Butyl Product Sheet

Highest Water Vapor/Gas Impermeability

Very Resistant to Ketones, Concentrated Oxidizing Acids, Concentrated Alkalis, and Salts

High Temperature Limit: 280°F

Shelf Life: 3 Years

Standard Length: 32" +/- 1 inch

*Any Length Requirements Other than Standard is Custom

*Call for Pricing

NAICS CODE: 339113

Butyl Material						
Long Gloves						
Part Number	Port Size	Thickness	Length	Hand Size	Hand Style	
6B1532-X	6" (150mm)	15 mil (0.4mm)	32" (812 mm)	8.5, 9.75, 10.5	A or L/R	
6B2432-X	6" (150mm)	24 mil (0.6mm)		8.5, 9.75, 10.5	A or L/R	
6B3032-X	6" (150mm)	30 mil (0.8mm)		8.5, 9.75, 10.5	A or L/R	
7B1532-X	7" (175mm)	15 mil (0.4mm)		9.75, U	A	
7B2432-X	7" (175mm)	24 mil (0.6mm)		9.75, U	A	
7B3032-X	7" (175mm)	30 mil (0.8mm)		9.75, U	A	
8B1532-X	8" (200mm)	15 mil (0.4mm)		8.5, 9.75, 10.5, U	A or L/R	
8B2432-X	8" (200mm)	24 mil (0.6mm)		8.5, 9.75, 10.5, U	A or L/R	
8B3032-X	8" (200mm)	30 mil (0.8mm)		8.5, 9.75, 10.5, U	A or L/R	
10B1532-X	10" (250mm)	15 mil (0.4mm)		8.5, 9.75, 10.5	A	
10B2432-X	10" (250mm)	24 mil (0.6mm)		8.5, 9.75, 10.5	A	
10B3032-X	10" (250mm)	30 mil (0.8mm)		8.5, 9.75, 10.5	A	
12B1532-X	12" (305mm)	15 mil (0.4mm)		9.75	A	
12B2432-X	12" (305mm)	24 mil (0.6mm)		9.75	A	
12B3032-X	12" (305mm)	30 mil (0.8mm)		9.75	A	
High Performance Butyl Material						
6BHP1532-X	6" (150mm)	15 mil (0.4mm)		32" (812 mm)	8.5, 9.75, 10.5	A or L/R
7BHP1532-X	7" (175mm)	15 mil (0.4mm)			9.75, U	A
8BHP1532-X	8" (200mm)	15 mil (0.4mm)	8.5, 9.75, 10.5, U		A or L/R	
10BHP1532-X	10" (250mm)	15 mil (0.4mm)	8.5, 9.75, 10.5		A	
13BHP1532-X	13" (330mm)	15 mil (0.4mm)	10.5		A	
Short Isolators						
B15-X		15 mil (0.4mm)	13" (330mm)	5, 6, 7, 8, 9, 10	A	
BHP15-X		15 mil (0.4mm)	13" (330mm)	5, 6, 7, 8, 9, 10	A	