

## CSM Product Sheet

High Resistance to UV Rays/Ozone/Natural Aging  
 Particularly Adapted when Hydrogen Peroxide and Per Acetic Acids are Used  
 Very Resistant to Reducing Acids, Diluted Acids, Alkalis, and Salts

Resistant to Reducing Acids

High Temperature Limit: 260°F

Shelf Life: 3 Years

Standard Length: 32" +/- 1 inch

\*Any Length Requirements Other than Standard is Custom

\*Call for Pricing

NAICS CODE: 339113

| <b>CSM Material</b>    |             |                |              |                    |            |
|------------------------|-------------|----------------|--------------|--------------------|------------|
| <b>Long Gloves</b>     |             |                |              |                    |            |
| Part Number            | Port Size   | Thickness      | Length       | Hand Size          | Hand Style |
| 6Y1532-X               | 6" (150mm)  | 15 mil (0.4mm) | 32" (812 mm) | 8.5, 9.75, 10.5    | A or L/R   |
| 6Y2432-X               | 6" (150mm)  | 24 mil (0.6mm) |              | 8.5, 9.75, 10.5    | A or L/R   |
| 7Y1532-X               | 7" (175mm)  | 15 mil (0.4mm) |              | 9.75, U            | A          |
| 7Y2432-X               | 7" (175mm)  | 24 mil (0.6mm) |              | 9.75, U            | A          |
| 8Y1532-X               | 8" (200mm)  | 15 mil (0.4mm) |              | 8.5, 9.75, 10.5, U | A or L/R   |
| 8Y2432-X               | 8" (200mm)  | 24 mil (0.6mm) |              | 8.5, 9.75, 10.5, U | A or L/R   |
| 10Y1532-X              | 10" (250mm) | 15 mil (0.4mm) |              | 8.5, 9.75, 10.5    | A          |
| 10Y2432-X              | 10" (250mm) | 24 mil (0.6mm) |              | 8.5, 9.75, 10.5    | A          |
| 12Y1532-X              | 12" (305mm) | 15 mil (0.4mm) |              | 9.75               | A          |
| 12Y2432-X              | 12" (305mm) | 24 mil (0.6mm) |              | 9.75               | A          |
| <b>Short Isolators</b> |             |                |              |                    |            |
| Y15-X                  |             | 15 mil (0.4mm) | 13" (330mm)  | 5, 6, 7, 8, 9, 10  | A          |
| Y24-X                  |             | 24 mil (0.6mm) | 13" (330mm)  | 5, 6, 7, 8, 9, 10  | A          |