

Neoprene & Electro-Static Dissipative Neoprene

Product Sheet

High Mechanical Properties (Tensile and Elongation)

Resistant to Hydrogen Peroxide

Resistant to Oil/Grease

High Dexterity/ Comfort

Poor Resistant to UV Rays

High Temperature Limit: 260°F

Shelf Life: 2 Years

Standard Length: 32" +/- 1 inch

*Any Length Requirements Other than Standard is Custom

*Call for Pricing

NAICS CODE: 339113

Neoprene Material					
Long Gloves					
Part Number	Port Size	Thickness	Length	Hand Size	Hand Style
6N1532-X	6" (150mm)	15 mil (0.4mm)	32" (812 mm)	6, 7, 8, 9, 10, 11	A
6N1532-X	6" (150mm)	15 mil (0.4mm)		6, 7, 8, 9, 10	L/R
6N2432-X	6" (150mm)	24 mil (0.6mm)		6, 7, 8, 9, 10, 11	A
6N2432-X	6" (150mm)	24 mil (0.6mm)		6, 7, 8, 9, 10	L/R
6N3032-X	6" (150mm)	30 mil (0.8mm)		6, 7, 8, 9, 10, 11	A
6N3032-X	6" (150mm)	30 mil (0.8mm)		6, 7, 8, 9, 10	L/R
7N1532-X	7" (175mm)	15 mil (0.4mm)		8, 9, 10, 11	A
7N1532-X	7" (175mm)	15 mil (0.4mm)		7, 8, 9, 10	L/R
7N2432-X	7" (175mm)	24 mil (0.6mm)		8, 9, 10, 11	A
7N2432-X	7" (175mm)	24 mil (0.6mm)		7, 8, 9, 10	L/R
7N3032-X	7" (175mm)	30 mil (0.8mm)		8, 9, 10, 11	A
7N3032-X	7" (175mm)	30 mil (0.8mm)		7, 8, 9, 10	L/R
8N1532-X	8" (200mm)	15 mil (0.4mm)		7, 8, 9, 10	A
8N1532-X	8" (200mm)	15 mil (0.4mm)		8, 9, 10	L/R
8N2432-X	8" (200mm)	24 mil (0.6mm)		7, 8, 9, 10	A
8N2432-X	8" (200mm)	24 mil (0.6mm)		8, 9, 10	L/R
8N3032-X	8" (200mm)	30 mil (0.8mm)		7, 8, 9, 10	A
8N3032-X	8" (200mm)	30 mil (0.8mm)		8, 9, 10	L/R
10N1532-X	10" (250mm)	15 mil (0.4mm)		9	A
10N2432-X	10" (250mm)	24 mil (0.6mm)		9	A
10N3032-X	10" (250mm)	30 mil (0.8mm)	9	A	
Electro-Static Dissipative Neoprene Material					
6ESDN1532-X	6" (150mm)	15 mil (0.4mm)	32" (812 mm)	6, 7, 8, 9, 10, 11	A
6ESDN1532-X	6" (150mm)	15 mil (0.4mm)		6, 7, 8, 9, 10	L/R
7ESDN1532-X	7" (175mm)	15 mil (0.4mm)		8, 9, 10, 11	A
7ESDN1532-X	7" (175mm)	15 mil (0.4mm)		7, 8, 9, 10	L/R
8ESDN1532-X	8" (200mm)	15 mil (0.4mm)		7, 8, 9, 10	A
8ESDN1532-X	8" (200mm)	15 mil (0.4mm)		8, 9, 10	L/R
10ESDN1532-X	10" (250mm)	15 mil (0.4mm)		9	A
Short Isolators					
N12-X		12 mil (0.3mm)	13" (330mm)	5, 6, 7, 8, 9, 10, 11	A
N15-X		15 mil (0.4mm)		5, 6, 7, 8, 9, 10, 11	A
N20-X		20 mil (0.5mm)		5, 6, 7, 8, 9, 10, 11	A
N24-X		24 mil (0.6mm)		5, 6, 7, 8, 9, 10, 11	A
N30-X		30 mil (0.8mm)		5, 6, 7, 8, 9, 10, 11	A
ESDN15-X		15 mil (0.4mm)		5, 6, 7, 8, 9, 10, 11	A